



Sludge Finder 2, a Blanket Improvement at Talybont.

Pulsar Measurement has supplied a Sludge Finder 2 sludge level measurement system as part of Welsh Water's Talybont-on-Usk treatment works developments, providing accurate measurement that allows optimization of sludge thickness and the production of a consistent solids content within the final sludge perfect for onward pumping and processing.

As often happens with instrumentation installations, the Sludge Finder is a small but vital component in a much larger project. In this case, the 70 MLD treatment works were supplied with a new DAF (dissolved air flotation) treatment process that leads on to a new sludge treatment facility where the Pulsar unit was sited. The sludge treatment plant features two picket fence thickeners treating the sludge from the DAF process plus dirty water from two other areas of the works. Polyelectrolyte is dosed into the feed to aid settlement and the final sludge is removed from the thickeners using positive displacement pumps.

Sludge Finder 2 was selected and installed by Black and Veatch, who chose it based on previous installations that had proven exceptionally reliable, giving them the

confidence that Sludge Finder 2 would successfully handle the mixture of sludges from different processes that gave a variable composition going into the thickeners.

Pulsar is the expert in acoustic technologies, supplying ultrasonic level and flow measurement globally. Sludge Finder 2 operates on a similar principle, featuring Pulsar's Viper self-cleaning transducer, which emits a sonar pulse that 'bounces' off the top of the sludge blanket. The key to the success of the Pulsar unit is its exceptionally sophisticated echo processing software that makes sense of the signal, possibly including numbers of competing and conflicting signals, to zero in on the accurate level. The Sludge Finder unit then gives several options of digital or analog outputs for alarm or control. At Talybont, the on-site SCADA system is used to remotely control pump operation to maintain the pumped sludge dry solids content at an extremely consistent 4%.

More Information

Sludge Finder 2 & Viper Transducer: <https://pulsarmeasurement.com/sludge-finder-2.html>



INFO@PULSARMEASUREMENT.COM

Pulsar Measurement is a trading name of Pulsar Process Measurement, Ltd.

Copyright © 2020 Pulsar Measurement
Registered Address: 1 Chamberlain Square CS, Birmingham B3 3AX
Registered No.: 3345604 England & Wales

Delivering the Measure of Possibility

United States

11451 Belcher Road South
Largo, FL 33773
+1 888-473-9546

Canada

16456 Sixsmith Drive
Long Sault, Ont. K0C 1P0
+1 855-300-9151

United Kingdom

Cardinal Building, Enigma
Commercial Centre
Sandy's Road, Malvern WR14 1JJ
+44 (0) 1684 891371

Rev 1.0