

AVFM 6.1 Area-Velocity Flow Meter

Approximate shipping weight: 11 lbs / 5 kg

STANDARD FEATURES:

QZ02L sensor: measures flow Velocity and Level simultaneously

Sensor cable: 25 ft / 7.6 m submersible, shielded 3-coaxial pairs

Flow rate range: 0.1 to 20 ft/sec and reverse flow to -5 ft/sec

 Accuracy: Velocity - $\pm 2\%$ of reading or ± 0.04 ft/sec (whichever is greater)

 Repeatability & Linearity $\pm 0.5\%$

 Level - $\pm 0.25\%$ of reading or ± 0.08 " (whichever is greater)

Repeatability & Linearity 0.1%

Enclosure: watertight, NEMA4X (IP66) polycarbonate

Display: white, backlit matrix

Totalizer: 14 digit

Calibration: built-in 5-key programmer

Outputs: three isolated 4-20mA/0-5V, Flow, Level and Velocity

2 control relays: 5 amp, SPDT - programmable for flow proportional pulse output, flow and/or level alarm

Datalogger: 128 Megabyte storage capacity (6.5 million points)

Power input: 100-240VAC 50/60Hz, 10 VA maximum

CE, UL/CSA/EN 61010-1

Model

Please configure model on next page



AVFM 6.1 Area-Velocity Flow Meter
Model
AVFM 6.1
POWER INPUT

Standard – 100-240VAC 50/60Hz, 10VA Maximum		A
9-32VDC, 10W Maximum		B

ENCLOSURE & ELECTRONICS PROTECTION

Standard NEMA4X (IP66) polycarbonate		1
NEMA4X polycarbonate enclosure with conformally coated electronics		2
CXJ8106 – Explosion proof NEMA7 (non-returnable & non-refundable)		3

ENCLOSURE TEMPERATURE RATING

Standard (-5° to 140°F / -20° to 60°C)		A
Heater and Thermostat 115VAC, 15 VA additional to Power Input (25 VA total)		B
Heater and Thermostat 230VAC, 15 VA additional to Power Input (25 VA total)		C

INTRINSIC SAFETY

Standard – QZ02L for non-hazardous locations only		1
QTY 3 ISB Intrinsic Safety Barriers for sensor installation in Class I, Div 1, Groups C,D; Class II, Groups E,F,G; Class III; Encl. Type 4		2

TRANSDUCERS (each with 25ft / 7.6m cable)

Standard – QZ02L submersible sensor, measures level and velocity		A1
PZ15-LP non-contacting level plus separate QZ02L-B-SS submersible velocity		B1
PZ15-LP Non-contacting Level plus SE4 Clamp-on Velocity		B2
PZ15 Non-contacting Level plus SE4 Clamp-on Velocity		F2

TRANSDUCER MOUNTING HARDWARE

Standard – Stainless steel mounting bracket (included with all Transducer options)		1
------------------------------------------------------------------------------------	--	---

TRANSDUCER CABLE LENGTH

Standard – 25 ft. 7.6m, cable type matches Transducer selection		A
50 ft / 15 m, cable type matches Transducer selection		B
100 ft / 30 m, cable type matches Transducer selection		C

SERIAL COMMUNICATIONS

Standard – None		1
Modbus® RTU via RS-485 or HART (field selectable)		2

CONTROL RELAYS

2 – Standard		A
4 Extra Relays (6 total), rated 5 amp SPDT, fully programmable		B

OPTIONS AND ACCESSORIES

Code	Description
VXC	Extra QZ02L sensor cable up to 500 ft / 152 m (submersible tri-coaxial, price is per ft)
DXC	Extra dual-coaxial sensor cable up to 500 ft / 152 m for optional QZ02L-B submersible velocity-only sensor (price is per ft)
XC	Extra coaxial sensor cable up to 500 ft/152 m for optional PZ15-LP level sensor (price is per ft)
JB2X	Sensor cable Junction Box, NEMA4X/IP66 polycarbonate
JB4X	Sensor cable Junction Box for separate level and velocity, NEMA4X/IP66
PM	Enclosure Panel Mount Flange assembly
SCR	Enclosure Sunscreen (iridite aluminum)
PZS	Sensor Sunscreen (for optional non-contacting PZ15-LP level sensor)
MB-QZ	Extra submersible sensor Mounting Bracket, stainless steel
MB15	Extra ultrasonic level Mounting Bracket, stainless steel
MNL	Additional Manuals (one supplied with each instrument)
SP4	Lightning/Surge Protection in NEMA13,12 Steel Enclosure
VSJ6	SS Pipe Mounting Band for 6"/152 mm ID pipes (fits $\pm 0.5"$ /13 mm)
VSJ8	SS Pipe Mounting Band for 8"/203 mm ID pipes (fits $\pm 0.5"$ /13 mm)
VSJ10	SS Pipe Mounting Band for 10"/254 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ12	SS Pipe Mounting Band for 12"/305 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ14	SS Pipe Mounting Band for 14"/356 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ15	SS Pipe Mounting Band for 15"/381 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ16	SS Pipe Mounting Band for 16"/406 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ18	SS Pipe Mounting Band for 18"/457 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ20	SS Pipe Mounting Band for 20"/508 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ24	SS Pipe Mounting Band for 24"/610 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ30	SS Pipe Mounting Band for 30"/762 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VSJ32-40	SS Half-Pipe Mounting Band for 32-40"/813-1016 mm ID pipes
VSJ42-54	SS Half-Pipe Mounting Band for 42-54"/1067-1372 mm ID pipes
VSJ56-72	SS Half-Pipe Mounting Band for 56-72"/1422-1829 mm ID pipes
VD6	SS Pipe Dam Band for 6"/152 mm ID pipes (fits $\pm 0.5"$ /13 mm)
VD8	SS Pipe Dam Band for 8"/203 mm ID pipes (fits $\pm 0.5"$ /13 mm)
VD10	SS Pipe Dam Band for 10"/254 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VD12	SS Pipe Dam Band for 12"/305 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VD14	SS Pipe Dam Band for 14"/356 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VD15	SS Pipe Dam Band for 15"/381 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VD16	SS Pipe Dam Band for 16"/406 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)
VD18	SS Pipe Dam Band for 18"/457 mm ID pipes (adjustable $\pm 0.5"$ /13 mm)

Replacement Sensors - Please provide instrument serial number when ordering replacements

Code	Description
QZ02L-SS-01-SD ¹	Standard submersible Velocity/Level Sensor, 316SS with 25 ft. / 7.6 m cable
QZ02L-SS-02-SD ¹	Optional submersible Velocity/Level Sensor, 316SS with 50 ft. / 15 m cable
QZ02L-SS-03-SD ¹	Optional submersible Velocity/Level Sensor, 316SS with 100 ft. / 30 m cable
QZ02L-SS-01-DP ¹	Submersible Velocity Sensor, 316SS with 25 ft. / 7.6 m cable
QZ02L-SS-02-DP ¹	Submersible Velocity Sensor, 316SS with 50 ft. / 15 m cable
QZ02L-SS-03-DP ¹	Submersible Velocity Sensor, 316SS with 100 ft. / 30 m cable
PZ15-LP ²	Non-contacting ultrasonic Level Sensor, PVC with 25 ft / 7.6 m cable
PZ15-LP-25XC ²	Non-contacting ultrasonic Level Sensor, PVC with 50 ft / 15 m cable
PZ15-LP-75XC ²	Non-contacting ultrasonic Level Sensor, PVC with 100 ft / 30 m cable
PZ15	Non-contacting ultrasonic Level Sensor, PVC with 25 ft / 7.6 m cable
PZ15-25XC	Non-contacting ultrasonic Level Sensor, PVC with 50 ft / 15 m cable
PZ15-75XC	Non-contacting ultrasonic Level Sensor, PVC with 100 ft / 30 m cable

¹ Sensors include MB-QZ mounting bracket

² Sensors include MB15 mounting bracket